



# Quantifying Performance of Non-Contact Fingerprinting

Stephen Fox, Ph.D.

Advanced Optical Systems, Inc.



# What is Live Scan?



# What is Live Scan?

- Mature Technology – Introduced in the 80s
- Stationary subject
- Provides slap, plain or rolled fingerprints
- The operator is in contact with the subject
- The subject is in contact with the device
- Does not address current understanding of cultural sensitivities

# What is Zero Contact Fingerprinting?



# What is Zero Contact Fingerprinting?

- Not so new....
- An operator may not be required
- Subject keeps moving
- The operator does not touch the subject
- Captures prints from platen unprintable users
- Addresses global cultural sensitivity concerns

# OTG in Operation



# How good Are Non-Contact Prints?



AOS Zero-Contact print



Live Scan print

# What are the differences?

## Platen Device

- Stops Motion
- Constrains Position
- Imposes Non-Linear enhancement
- Distorts Geometry

## Non-Contact Device

- Stops Motion
- Constrains Position
- Provides sufficient contrast
- Distorts Geometry



# Quantifying Performance

- FBI Certification is the *de facto* standard
  - Image Quality, Human Examiner, Stress testing, User Experience, Pilot Study
- Image Quality Assessment
- Certified Human Examiner Reports
- Homogeneous Error Rates
- Heterogeneous Error Rates

# In One Minute

## Platen Device

- Operator begins working with one subject



## Non-Contact Device

- Up to 50 people have provided four fingerprints each




# Image Quality Metrics

- Signal to Noise Ratio (shot noise limit)
- Uniformity (ambient lighting control)
- Grey Scale Distribution (contrast extraction)
- MTF (boundaries and motion)
- Geometric Distortion (imager -> object)

# Perspective Distortion


- All contact based scanners distort fingerprints
- Matching software consequently deals with distortions, and has done so quite effectively
- The 3D fingerprinting world also tried to solve the distortion issue using hardware and imaging techniques
- Software won

# Impact of Distortion



# Area

- AOS Non-contact captures more than typical flats, but not as much as rolled
- Increased area means lower error rates
- Delta regions
- Right side/Left side Issues



# MTF

- Based on typical finger topology... approximately 45 degree max angle
- Perspective Distortion indicates an MTF frequency compression of 1.4 at 45 degree angle of incidence
- Have to get the discrete sampling rate and analog resolution balance right

# Pilot Studies

- Certified Human Examiner Considerations
- Homogeneous Matching Error Rates
- Heterogeneous Matching Error Rates
- The “invisible” subjects
  - [http://www.hindawi.com/journals/bmri/  
2012/626148/](http://www.hindawi.com/journals/bmri/2012/626148/)
  - [http://www.timegoesby.net/weblog/2013/09/  
elders-and-fingerprint-technology.html](http://www.timegoesby.net/weblog/2013/09/elders-and-fingerprint-technology.html)

# Pilot Studies

- NIJ Sponsored Study
- WVU De-duplicated

Probe Set	Gallery Set	True Match Rank 1	
CMR2	CMR2	100%	Reference
SEEK Rolled	CMR2	98%	Contact Rolled
SEEK Plain	CMR2	95%	Contact Plain
BioSled Plain	CMR2	94%	Contact Plain
OTG 1.0+	CMR2	92%	Non-contact Plain
FOTF	CMR2	92%	Non-contact Plain
TBS HT1	CMR2	92%	3D Non-contact

# Research Interests

- High Quality Interoperability Data
- NFIQ 2.0
- Improving Scans on the 5 to 10 Percent
- Comparison to 3D Topographic Scans
- Impact of Ridge Phase and Shadowing
- Impact of 3D Objects/Targets

# Working Together...



# Suitcase Points

- Non-contact prints are reliable and trustworthy for verification and authentication
- Image quality tests and methodologies do not differ significantly from platen based technologies
- High user acceptance
- Pilot studies and CRADA research topics are welcome

# Contact Information

- Stephen Fox, PhD
- Advanced Optical Systems, Inc
- [Fox@aos-inc.com](mailto:Fox@aos-inc.com)
- 1-256-971-0036