

SRDK-408D
COLD HEAD

5.83

(2) LIFTING EYE BOLTS
WITH 1/4-20 THREADS

INSTRUMENTATION SKIRT

COMMON VACUUM
PORT

6.0 O.D. X .125 W (AL)
[152.4mm]

4.0 O.D. (AL)
[101.6mm]

30.91
[785.06mm]

(6) 1/4-20 TAP DRILL X .50 DP.
& TAP X .375 DP. HOLES EQ. SP.
ON A 6.375 DIA. B.C. FOR
CUSTOMER USE

0.75
[19.05mm]

2.52 DIA. COLD FINGER W/(6)
M5 TAPPED HOLES EQ. SP.
ON A 2.128 DIA. B.C. WITH
SENSOR INSTALLED

11.50 [292.1mm] O.D.

3.50-24
THREAD X.188 LG

COLD FINGER EXTENSION
WITH (2) 10-32 TAPPED
HOLES (HELICOIL) SP ON
A .50 DIA .B.C AS SHOWN

2.875-24
THREAD X .188 LG

2.75
[69.85mm]

1.75
[44.45mm]

10.25
[260.35mm]

2.00

90mm

4.00
[101.59mm]

.040W

.030W

70mm

6.00
[152.40mm]

3.00 O.D.

3.75 O.D.

8.94 O.D.

1.00 [25.4mm]

250mm SQUARE
BOTTOM FLANGE

(4) CLEAR HOLES FOR
1/4-20 ON A 9.05 [230mm]
BOLT SQUARE [325.3mm BCD]