



Progress of NIM's Smoke Stack Simulator and Field Measurement in Power Plants

Liang Zhang,
National Institute of Metrology, China

01

Background

02

Smokestack Simulator of NIM China

03

Field Calibration System

04

Field Tests

05

Future Works

Need for Stack Gas Flowrate Measurement

□ Industry plant efficiency test

□ Air pollution emission monitoring

- Chinese Environmental Protection Agency has clear demand for accurate flue gas flowrate measurement

□ Carbon trading

- In 2013, China has carried out pilot carbon trading in 7 provinces, and extended to the national carbon trading market in 2017
- In 2013 NDRC issued first 10 industry sectors greenhouse gas emission accounting methods and reporting guidelines

Measurement and Calibration Scheme

□ Industry plant efficiency test

- S type pitot tube point by point measurement
- Wind tunnel calibration at 0 pitch and 0 yaw angle

□ Air pollution emission monitoring

- On site velocity comparison using S type pitot tube.
- Wind tunnel calibration at 0 pitch and 0 yaw angle

□ Carbon trading

- Fuel based calculation method

Overall Research Plan

□ Stack flowrate calibration

- Build calibration facilities to calibrate standard 3D pitot tubes in different flow conditions
- Study the pitot tube integration method
- Field calibration system

□ Stack ultrasonic flowmeter calibration

- Dry calibration
- Real flow velocity calibration

□ Field tests

01

Background

02

Smokestack Simulator of NIM China

03

Field Calibration System

04


Field Tests

05

Future Works

Smoke Stack Simulator of NIM


Working Standard



Smoke Stack Simulator of NIM



Reference Section & Wind Tunnel



- Velocity range of wind tunnel: 0.5~70m/s
- Turbulence intensity: 0.75%@50m/s

NIM's Dual LDA Flowrate Standard


Standard Flowmeters
Nozzle and
Turbine Flowmeters



Vacuum Pump


Dual LDA Test Windows
(Downstream of Contraction)

NIM's Dual LDA Flowrate Standard



NIM's Dual LDA Flowrate Standard

□ Boundary layer LDV




Reference Section & Wind Tunnel

□ LDV primary standard of SMSS




Reference Section & Wind Tunnel

□ LDV seeding




Reference Section & Wind Tunnel

□ Wind tunnel



PIV



Reference Section & Wind Tunnel

- 8-path USM working standard




Reference Section & Wind Tunnel

- ❑ USM lost signal
- ❑ Electromagnetic interference



Test Section



Test Section



□ Contraction section and swirl generator



Test Section

□ USM under test

- **Circular: 8-path (OWICS) + dual cross diametric path**
- **Rectangular: 8-path (OWIRS) + dual cross diametric path**





Test Section

□ USM under test



Test Section

□ Pitot tube automatic transverse system



Test Section

□ Pitot tube automatic transverse system




Test Section

□ Fans



Test Data

□ Flow stability



Test Data

LDV calibrate USM

Set flowrate (m³/h)	750	1700	3500	8500	17000	32000	50000	80000
Velocity in the Center of the pipe (m/s)	0.5	1	2	5	10	20	30	50
LDV flowrate (Nm³/h)	755.467	1684.68	3494.48	8496.88	17375.7	32617.2	50932.2	84476.6
USM flowrate (Nm³/h)	745.971	1681.39	3517.49	8588.96	17542.3	32830.1	51358.4	84381.5
Indication error	1.26%	0.19%	-0.66%	-1.08%	-0.96%	-0.65%	-0.84%	0.11%

01

Background

02

Smokestack Simulator of NIM China

03

Field Calibration System


04

Field Tests

05


Future Works

Field Calibration System




Field Calibration System

□ Geometric calibration device




80mm



1st Generation


2nd Generation



Field Calibration System


□ Geometric calibration device

2nd Generation



Field Calibration System

□ Automatic pitot tube positioning system



01

Background

02

Smokestack Simulator of NIM China

03

Field Calibration System

04


Field Tests

05

Future Works

Field Tests

□ Pitot tubes calibration in NIST wind tunnel



Field Tests


□ Natural gas power plant



Install 6-Path
Ultrasonic Flowmeter



Pitot Tube
Test
Platform





Field Tests

□ Natural gas power plant




Field Tests


❑ Coal-fired power plant



Field Tests



Field Tests



Field Tests




Field Tests




Field Tests

□ Coal-fired power plant – 3D laser scanner



Comparison




Field Tests

- ❑ Coal-fired power plant – 3D laser scanner




Field Tests

□ Coal-fired power plant – 3D laser scanner




Field Tests

Coal-fired power plant – Flowrate Measurement



Field Tests


Coal-fired power plant – Flowrate Measurement



Field Tests

Coal-fired power plant – Flowrate Measurement by pitot tube @


10Hz



Field Tests

Coal-fired power plant – Flowrate Measurement


Differential Pressure 1-2



Field Tests

□ Coal-fired power plant – Flowrate Measurement

Differential Pressure 1-2



01

Background

02

Smokestack Simulator of NIM China

03

Field Calibration System

04


Field Tests

05

Future Works


Future Work

- Close loop wind tunnel which can change the gas composition (simulated flue gas) and temperature.



Future Work

□ Dry calibration facility for flue gas USM



Future Work

❑ Other industry sectors (test 30 sites in 3 years)

- Cement production
- Glass production
- Ceramic production
- Chemical production
- Non-ferrous metal production
- Iron and steel production



Thank you for your attention

zhangliang@nim.ac.cn