

USGv6 Test Selection Tables*

DHCP Client

I4-Interoperability: DHCP-Client-v1.1

Applicable Profile: NIST SP 500-267 A profile for IPv6 in the U.S. Government - Version 1.0, July 2008.

Configuration Option: DHCP-Client

Test Specification Id:

- [\[DHCPv6-Interoperability\]](#) IPv6 Ready DHCPv6 Interoperability Test Suite, Revision 1.1.1 , [editor: [IPv6 Ready Logo](#)].

Reference:

- [RFC 3315]Droms, R. J. Bound, B. Volz, T. Lemon, C. Perkins, M. Carney, Dynamic Host Configuration Protocol for IPv6 (DHCPv6), July, 2003

Interoperability Partner Requirements:

- Any host or router claiming compliance with the USGv6 profile MUST demonstrate evidence of interoperability with **three** or more independent implementations of IPv6. The three implementations must include at least one Host and at least one Router.
- Can not change Target nodes once testing has begun.

DHCPv6-Interoperability

If your Device Under Test (DUT) Type is **Host**:

- DUT = TAR-Client1 for all tests.
- TAR-Server1 = Independent Implementation Device B
- TAR-Relay-Agent1 = Independent Implementation Device C
- Third Interoperability Partner is satisfied by executing the test specification again using the following:
 - TAR-Server1 = Independent Implementation Device D

DHCP Client Test Check List			
Reference	Test Specification Id	Test Number	Device Type
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.1: DHCPv6 Initialization	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.2: Client Initiated: Transmission of Confirm messages	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.3: Client Initiated: Transmission of Renew messages	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.4: Client Initiated: Transmission of Rebind messages	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.5: Client Initiated: Transmission of Release messages	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.6: Client Initiated: Transmission of Decline messages	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.7 Server Initiated: Transmission of Advertise messages with NoAddrsAvail	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.8: Server Initiated: Transmission of Reply messages with NotOnLink	Host
RFC 3315	DHCPv6-Interoperability	DHCPInterop.1.9: Relay-Agent Basic Message Exchanges (A) (B) (C) (D) (E) (F)	Host

* The objective of this test selection sheet is to provide a reference for available test specifications that identifies tests applicable to the USGv6 Profile.